




P: 1.800.999.1700 | F: 610.459.1084 | info@westlakeplastics.com | 490 West Lenni Road, Lenni, PA 19052 U.S.A.

Arolux® PEEK WM



Arolux® Polyetheretherketone (PEEK) is a semi-crystalline thermoplastic offering a combination of high temperature resistance, good wear and abrasion resistance, excellent dimensional stability and exceptional chemical resistance. The tensile and flexural properties of PEEK are among the highest of all thermoplastic resins. PEEK is an outstanding electrical insulator offering superior dielectric strength. In thinner gauge film (~0.10» and less) PEEK material will be translucent. As gauge increases, the material will become opaque beige in appearance.

INDUSTRY




Aerospace &
Defense



Chemical Process



Life Sciences



Semiconductor and
ESD

COLORS AVAILABLE



Natural

ATTRIBUTES



Biocompatibility



Stiffness



Strength



Chemical Resistance



Heat Resistant



Wear Resistance



SHAPES

Extruded Sheet



Extruded Film





P: 1.800.999.1700 | F: 610.459.1084 | info@westlakeplastics.com | 490 West Lenni Road, Lenni, PA 19052 U.S.A.

Arolux® PEEK WM

TYPICAL PROPERTIES

PROPERTY	TEST STANDARD	ENGLISH UNITS	METRIC UNITS
Mechanical			
Tensile Modulus	ASTM D638	508,000 psi	3500 MPa
Tensile Strength @ Yield	ASTM D638	13,800 psi	95 MPa
Tensile Elongation @ Yield	ASTM D638	5.2 %	5.2 %
Flexural Modulus	ASTM D790	537,000 psi	3700 MPa
Flexural Strength	ASTM D790	21,200 psi	146 MPa
Notched Izod Impact	ASTM D256	1.7 ft.-lb./in	0.091 kJ/m
Thermal			
HDT @ 264 psi (annealed)	ASTM D648	315 F	157 C
Glass Transition Temperature	ASTM D3418	302 F	150 C
Physical			
Specific Gravity	ASTM D792	1.30	1.30

*Data above is based on testing of injection molded test specimens



P: 1.800.999.1700 | F: 610.459.1084 | info@westlakeplastics.com | 490 West Lenni Road, Lenni, PA 19052 U.S.A.

Arolux® PEEK WM

PRODUCT SHAPES & DIMENSIONS

Extruded Sheets: 48"W x 96"L (122cm x 244cm)

0.03" (0.76mm)	0.035" (0.89mm)	0.06" (1.52mm)	0.062" (1.57mm)	0.08" (2.03mm)	0.09" (2.29mm)
0.095" (2.41mm)	0.125" (3.18mm)	0.1875" (4.76mm)	0.25" (6.35mm)		

Extruded Sheets: 24"W x 48"L (61cm x 122cm)

0.75" (19.05mm)	1.0" (25.4mm)	1.5" (38.1mm)	2.0" (50.8mm)
-----------------	---------------	---------------	---------------

Extruded Films: 26"W (66cm)

0.002" (0.05mm)	0.003" (0.08mm)	0.004" (0.1mm)	0.005" (0.13mm)	0.010" (0.25mm)	0.020" (0.51mm)
-----------------	-----------------	----------------	-----------------	-----------------	-----------------

LAST REVISED: 01/30/2025

This information is offered solely for your consideration, examination and verification, and is to be construed neither as a warranty nor guarantee that the same results as those stated herein will be obtained by the use to which others may put the material. Each user of the material should make his own tests to determine the characteristics and suitability of the material for his own particular use and the use which will be made of the completed product. This publication is not to be taken as a license to operate under, or a recommendation to infringe any patents. The observance of all legal regulations and patents is the responsibility of the user. The buyer's exclusive remedy against the seller shall be for the repair or replacement of defective stock. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or other incidental or consequential loss) shall be available to the buyer.

EXCLUSION OF WARRANTIES: THERE ARE NO WARRANTIES AS TO THE MATERIAL DESCRIBED HEREIN, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. ANY VALUES STATED IN SELLER'S LITERATURE ARE TYPICAL PROPERTIES ONLY.