



P: 1.800.999.1700 | F: 610.459.1084 | info@westlakeplastics.com | 490 West Lenni Road, Lenni, PA 19052 U.S.A.

Radel® WM



Radel® Polyphenylsulfone (PPSU) is an amorphous transparent high performance thermoplastic. It is known for its high heat resistance, extreme toughness, high flexural and tensile strength, excellent hydrolytic stability and good resistance to a broad range of chemicals including aqueous mineral acids, bases, and oxidizing agents and most solvents. Additionally, PPSU is inherently flame resistant.

INDUSTRY



Aerospace &
Defense



Life Sciences

COLORS AVAILABLE



Black



Blue



Bone



Brown



Dark Grey



Green



Grey



Light Grey



Natural



Orange



Purple



Red



Yellow

ATTRIBUTES



Biocompatibility



Heat Resistant



Dimensional Stability



Chemical Resistance



Impact Resistance



SHAPES

Extruded Slab



Extruded Sheet



Extruded Film



Extruded Rod





P: 1.800.999.1700 | F: 610.459.1084 | info@westlakeplastics.com | 490 West Lenni Road, Lenni, PA 19052 U.S.A.

Radel® WM

TYPICAL PROPERTIES

PROPERTY	TEST STANDARD	ENGLISH UNITS	METRIC UNITS
Mechanical			
Tensile Strength @ Yield*	D638	11.6 kpsi	79.9 MPa
Tensile Strength @ Break*	D638	9.9 ksi	68.3 MPa
Tensile Elongation @ Yield*	D638	7.4 %	7.4 %
Tensile Elongation @ Break*	D638	23.7 %	23.7 %
Tensile Modulus*	D638	355 kpsi	2448 MPa
Flexural Strength* - 5%	D790	14.4 kpsi	99.3
Flexural Modulus*	D790	337 kpsi	2,323 MPa
Izod Impact Resistance - Notched* D256		3.06 ft-lb/in	163 J/m
Thermal			
HDT** @ 264 psi	D648	404 °F	207 °C
Physical			
Moisture Absorption**	D570	0.37 %	0.37 %
Specific Gravity**	D792	1.29	1.29
Other			

*Data above is based on testing of machined test specimens made from extruded bar stock

**Data above is based on testing of injection molded test specimens



P: 1.800.999.1700 | F: 610.459.1084 | info@westlakeplastics.com | 490 West Lenni Road, Lenni, PA 19052 U.S.A.

Radel® WM

PRODUCT SHAPES & DIMENSIONS

Rods: 48"L (122cm)

2.25" (57.15mm)	2.50" (63.5mm)	2.75" (69.85mm)	3" (76.2mm)	3.25" (82.55mm)	3.50" (88.9mm)
3.75" (95.25mm)	4" (101.6mm)	4.25" (107.95mm)	4.50" (114.3mm)	4.75" (120.65mm)	

Rods: 96"L (244cm)

0.5" (12.7mm)	0.75" (19.05mm)	1" (25.4mm)	1.25" (31.75mm)	1.50" (38.1mm)	1.75" (44.45mm)
2" (50.8mm)					

Extruded Slabs: 24"W (61cm)

0.5" (12.7mm)	0.75" (19.05mm)	1" (25.4mm)	1.25" (31.75mm)	1.5" (38.1mm)	1.75" (44.45mm)
2" (50.8mm)	2.25" (57.15mm)	2.50" (63.5mm)	2.75" (69.85mm)	3" (76.2mm)	3.25" (82.55mm)
3.50" (88.9mm)	3.75" (95.25mm)	4" (101.6mm)			

Extruded Sheets: 48"W x 96"L (122cm x 244cm)

0.03" (0.76mm)	0.035" (0.89mm)	0.06" (1.52mm)	0.062" (1.57mm)	0.08" (2.03mm)	0.09" (2.29mm)
0.095" (2.41mm)	0.125" (3.18mm)	0.1875" (4.76mm)	0.25" (6.35mm)		

Extruded Films: 26"W (66cm)

0.002" (0.05mm)	0.003" (0.08mm)	0.004" (0.1mm)	0.005" (0.13mm)	0.01" (0.25mm)	0.02" (0.51mm)
-----------------	-----------------	----------------	-----------------	----------------	----------------

LAST REVISED: 01/30/2025

This information is offered solely for your consideration, examination and verification, and is to be construed neither as a warranty nor guarantee that the same results as those stated herein will be obtained by the use to which others may put the material. Each user of the material should make his own tests to determine the characteristics and suitability of the material for his own particular use and the use which will be made of the completed product. This publication is not to be taken as a license to operate under, or a recommendation to infringe any patents. The observance of all legal regulations and patents is the responsibility of the user. The buyer's exclusive remedy against the seller shall be for the repair or replacement of defective stock. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or other incidental or consequential loss) shall be available to the buyer.

EXCLUSION OF WARRANTIES: THERE ARE NO WARRANTIES AS TO THE MATERIAL DESCRIBED HEREIN, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. ANY VALUES STATED IN SELLER'S LITERATURE ARE TYPICAL PROPERTIES ONLY.