



P: 1.800.999.1700 | F: 610.459.1084 | info@westlakeplastics.com | 490 West Lenni Road, Lenni, PA 19052 U.S.A.

Styrclear®



Styrclear is made from resin that is suitable for use in certain food contact applications, contact your local Westlake Plastics representative for specific regulatory declarations. Styrclear is a rigid plastic that is often used in products that require clarity, such as food packaging and laboratory ware. Styrclear is a cost-effective, versatile thermoplastic that is known for being lightweight and easy to print on. For this reason, it is a great choice for POP display and indoor signage, among other common displays.

INDUSTRY



Engineering

COLORS AVAILABLE



Transparent

ATTRIBUTES

 Transparent



 Food Contact



SHAPES

Compression Sheet



Extruded Rod





P: 1.800.999.1700 | F: 610.459.1084 | info@westlakeplastics.com | 490 West Lenni Road, Lenni, PA 19052 U.S.A.

Styrclear®

TYPICAL PROPERTIES

PROPERTY	TEST STANDARD	ENGLISH UNITS	METRIC UNITS
Mechanical			
Flexural Modulus	D790	470 kpsi	3,241 MPa
Flexural Strength - 5%	D790	13 kpsi	90 MPa
Izod Impact Resistance - Notched	D256	0.40 ft-lb/in	0.021 kJ/m
Tensile Elongation @ Break	D638	3.00 %	3.00 %
Tensile Modulus	D638	460 kpsi	3,172 MPa
Tensile Strength @ Break	D638	7.5 kpsi	52 MPa
Tensile Strength @ Yield	D638	7.5 kpsi	52 MPa
Thermal			
HDT @ 264 psi	D648	192 °F	89 °C
HDT @ 64 psi	D648	208 °F	98 °C
Physical			
Specific Gravity	D792	1.04	1.04

*Data above is based on testing of injection molded test specimens



P: 1.800.999.1700 | F: 610.459.1084 | info@westlakeplastics.com | 490 West Lenni Road, Lenni, PA 19052 U.S.A.

Styraclear®

PRODUCT SHAPES & DIMENSIONS

Rods: 48"L (122cm)

2.25" (57.15mm)	2.5" (63.5mm)	2.75" (69.85mm)	3" (76.2mm)	3.25" (82.55mm)	3.5" (88.9mm)
3.75" (95.25mm)	4" (101.6mm)				

Rods: 96"L (244cm)

0.5" (12.7mm)	0.75" (19.05mm)	1" (25.4mm)	1.25" (31.75mm)	1.5" (38.1mm)	1.75" (44.45mm)
2" (50.8mm)					

Compression Sheets: 24"W x 48"L (61cm x 122cm)

0.25" (6.35mm)	0.375" (9.53mm)	0.5" (12.7mm)	0.75" (19.05mm)	1" (25.4mm)	1.25" (31.75mm)
1.5" (38.1mm)	1.75" (44.45mm)	2" (50.8mm)			

LAST REVISED: 01/30/2025

This information is offered solely for your consideration, examination and verification, and is to be construed neither as a warranty nor guarantee that the same results as those stated herein will be obtained by the use to which others may put the material. Each user of the material should make his own tests to determine the characteristics and suitability of the material for his own particular use and the use which will be made of the completed product. This publication is not to be taken as a license to operate under, or a recommendation to infringe any patents. The observance of all legal regulations and patents is the responsibility of the user. The buyer's exclusive remedy against the seller shall be for the repair or replacement of defective stock. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or other incidental or consequential loss) shall be available to the buyer.

EXCLUSION OF WARRANTIES: THERE ARE NO WARRANTIES AS TO THE MATERIAL DESCRIBED HEREIN, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. ANY VALUES STATED IN SELLER'S LITERATURE ARE TYPICAL PROPERTIES ONLY.